

Round 5 results — Run xj4wang_run3 submitted from xj4wang




Run Description

The retrieval model used is BMI (Baseline Model Implementation), provided as a starter by Gordon Cormack for the TREC 2015/2016 Total Recall Track, with human assessors in place of the server (manual processing). [1] In more detail: It uses the CAL (Continuous Active Learning) method, starting with 1 synthetic file created using the given topics, word for word. This method is described by Grossman and Cormack in [4]. Feature vectors are created using the BMI tools. [1] SofiaML is used as the learner. The weighting scheme were chosen heavily based on the work of Cormack and Grossman in [2]. Stopping conditions for manual labeling were chosen heavily based on the work of Grossman et al. in [3]. References: [1] <https://cormack.uwaterloo.ca/trecvm/> [2] <file:///C:/Users/Jean/Downloads/2600428.2609601.pdf> [3] <https://trec.nist.gov/pubs/trec25/papers/Overview-TR.pdf> [4] https://cormack.uwaterloo.ca/caldemo/AprMay16_EdiscoveryBulletin.pdf


Summary Statistics	
Run ID	xj4wang_run3
Topic type	manual
Contributed to judgment sets?	yes

Overall measures	
Number of topics	50
Total number retrieved	49928
Total relevant	10910
Total relevant retrieved	5743
MAP	0.2448
Mean Bpref	0.4912
Mean NDCG@20	0.6663
Mean RBP(p=0.5)	0.7767 +0.0018

Document Level Averages	
	Precision
At 5 docs	0.8640
At 10 docs	0.8080
At 15 docs	0.7307
At 20 docs	0.6780
At 30 docs	0.6247
R-Precision	
Exact	0.2984




Per-topic difference from median bpref for all Round 4 runs




Per-topic difference from median NDCG@20 for all Round 4 runs

Round 5 results — Run xj4wang_run3 submitted from xj4wang



Topic
Per-topic difference from median P@20 for all Round 4 runs



Topic
Per-topic difference from median RBP(p=0.5) for all Round 4 runs